



## SUNOCO SUPER C GOLD ELITE 5W-40 CK-4

### OVERVIEW

**SUNOCO SUPER C GOLD ELITE 5W-40 CK-4** is formulated to meet or exceed the latest API diesel engine oil specifications, as well as the warranty and performance requirements of most diesel engine manufacturers. This full synthetic product is for use in model year 2017 and newer heavy-duty diesel engines in severe, high-output service, and is fully backwards compatible to engines requiring any API C service class engine oil.

### FEATURES & BENEFITS

**SUNOCO SUPER C GOLD ELITE 5W-40 CK-4** is a superior product that has a unique formulation composed of full synthetic base stocks. It is designed for superior anti-oxidation characteristics with enhanced high temperature capabilities and superior low temperature flow properties. It has increased shear stability and improved fuel economy to ensure long service life in adverse conditions and provides robust protection over any previous API category.

### APPLICATIONS

**SUNOCO SUPER C GOLD ELITE 5W-40 CK-4** can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, stationary equipment, and any vehicle or diesel engine where an API CK-4 or earlier C class oil is specified.

### SPECIFICATIONS

**API CK-4, CJ-4, CI-4, CI-4 Plus, CH-4/SN • ACEA E9-16, E9-08 & E7-04 • CAT ECF-1a, ECF-2, ECF-3 & TO-2 • Cummins CES 20086, 20081, 20077 & 20076 • Detroit Diesel DDC 93K222, 93K218, 93K214, 7SE270, PG PGOS • Deutz DQC III-10 LA • Ford WSS-M2C171-F1 • JASO DH-2 • Mack EOS-4.5, EO-O Premium Plus, EO-M, EO-N Premium Plus • MB 228.31 • MAN 3575 • MTU MTL 5044 Type 2.1 • Renault VI RLD-4, RLD-3 • Volvo VDS-4.5, VDS-4, VDS-3, VDS-2**

### TYPICAL PROPERTIES

<b>Product Code</b>	<b>3303</b>
CCS, cP (@ -20°C)	6250
Viscosity, cSt @ 100°C	15.3
Viscosity, cSt @ 40°C	93.9
Viscosity Index	172
Pour Point, °C	-42
Sulfated Ash, Wt. (%)	1.0
Calcium, Wt. (%)	.130
Phosphorous, Wt. (%)	.110
TBN (D2896)	10